

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:****Timco Engineering, Inc.  
849 NW State Road 45  
P.O. Box 370,  
Newberry, FL 32669****Date of Grant: 06/08/2007****Application Dated: 06/07/2007****MaxStream Inc.  
355 South 520 West  
Suite 180  
Lindon, UT 84042****Attention: David Steed , Vice President - Engineering****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is  
VALID ONLY for the equipment identified hereon for use under the Commission's  
Rules and Regulations listed below.

**FCC IDENTIFIER:** OUR-XBEE**Name of Grantee:** MaxStream Inc.**Equipment Class:** Digital Transmission System**Notes:** XBee OEM RF Module

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
20	15C	2405.0 - 2480.0	0.001		

Limited Modular Approval. Power output is conducted and measured at the antenna terminal. This is an OEM transmitter module approved for use in products operating as a mobile transmitting device with respect to 2.1091. MPE compliance was demonstrated with a typical antenna(s) gain as shown in this filing. Final antenna installation and operating configurations of this transmitter including antenna gain and cable loss must not exceed the EIRP of the configuration used for MPE compliance. Professional installation is required for those antenna(s) installations using standard connectors. Products operating with this module are required to provide a minimum separation distance of 20cm. Grantee must coordinate with OEM integrators to ensure the end-users of products operating with this module are provided with operating instructions to satisfy RF exposure requirements. Separate approval is required for all other operating configurations, including portable configurations with respect to 2.1093 and different antenna configurations.

20: All electrical and mechanical devices employed for spurious radiation suppression, including any modifications made during certification testing, must be incorporated in each unit marketed.