

## SPECIFICATIONS 2017

### Digi HCgateway Wireless Gateway

Digi HCgateway is the central hub of the Digi SafeTemps automated food temperature monitoring system. Once the temperature reading is confirmed, the recorded data is logged and sent to the Wi-Fi Digi HCgateway that processes and saves it to the cloud for easy, up-to-the-minute compliance reporting and long-term storage.



### Features

- Temperature data reported every 10 minutes.
- Automatically pairs with all Digi sensors within range.
- Data is securely transmitted to web-based app.
- Exceeds reporting requirements.

### Specifications

• Communication Range	300+ feet line of sight*
• Communication Method	802.11 b/g/n
• Transmission Frequency	5 minute intervals
• Power Source	Inputs from 9 to 60V AC or DC
• Common Power Sources	12V DC wall charger; 24V AC security camera power supply; 12V reefer unit battery
• Cable Options	12V DC adapter; reefer trailer cable
• Physical Dimensions/Weight	2.25" x 2.5" x 1.5"; 3.2 oz
• Wireless Standard	802.11 b/g/n
• IP Address	Obtained from DHCP server
• Security Protocol	802.11i (WEP, WPA1-TKIP, WPA1-AES, WPA2-AES, WPA2-Mixed)
• Outgoing Network Destinations	novotrace.com (port 80), www.bn-gateway.com (port 80)
• Communication Direction	Outbound, no inbound
• Average Data Load (Typical Install Up To 100 HCsensors)	<5 MB per month

\* Actual communication distance will depend on RF environment

For more information about Digi HCgateway  
visit [www.digi.com/smart-solutions](http://www.digi.com/smart-solutions)

1-866-806-2653