

SPECIFICATIONS 2017

Digi Smart Gateway Wireless Gateway

Digi Smart Gateway is the central communications and GPS hub of the Digi SafeTemps automated temperature monitoring solution for transportation and logistics. Temperature and location are recorded wirelessly via Digi Sensors and Digi Data Loggers. Data is then sent to the Digi SafeTemps platform over wireless cellular communication.

Features

- Measures temperatures at point-of-product.
- Serves as independent audit of refrigeration system.
- Provides real-time documentation.
- Exceeds FSMA reporting requirements.



Specifications

- | | |
|------------------------|---|
| • Communication Method | BLE, WLAN: 802.11 a/b/g/n, Cellular: LTE/3G |
| • Power Source | Inputs from 9 to 36V DC |
| • Common Power Sources | 12VDC (1.5A) wall adapter, 12V reefer unit battery |
| • Cable Options | 12V DC adapter; Reefer trailer cable |
| • Physical Dimensions | 6.73" x 4.76" x 2.17" |
| • IP Rating | IP65 |
| • IP Address | Client mode: DHCP assigned, AP mode: Fix address, assigns IP addresses via DHCP to attached clients |
| • Security Protocol | (WPA, WPA2/WEP/etc) |

For more information about Digi Smart Gateway
visit www.digi.com/smart-solutions

1-866-806-2653