

## SPECIFICATIONS 2017

### Digi Smart Humidity Guard Wireless Thermometer

Digi Smart Humidity Guard monitors temperature and humidity 24/7/365 for areas where temperature documentation, humidity documentation, and alerts are needed.



#### Features

- 24/7/365 monitoring of equipment.
- 24/7/365 notification of alerts sent via email, text, and/or phone call.
- Identifies potential equipment maintenance issues in advance of failure.
- Wireless transmission eliminates the need for hard wired installation.

#### Specifications

• Display	128x32 pixel graphical backlit LCD
• Temperature Range	32°F to 176°F (0°C to 80°C)
• Accuracy	±2°F (±1.11°C)
• Resolution	0.1°F/C
• Humidity Range	0 to 100% RH
• Humidity Accuracy	±3% RH
• Backlight	Yes
• Fahrenheit/Celsius	Yes
• Sleep Mode	Yes
• Distance	5,000 feet line of sight*
• Batteries	3 AA
• Battery Life	12 months
• Calibration	NIST traceable Certificate (optional)
• Dimensions	4" x 3" x 1"
• Weight	5.4 oz
• Compliances	RoHS/FCC/IC

\* Actual communication distance will depend on RF environment

For more information about Digi Smart Humidity Guard  
visit [www.digi.com/smart-solutions](http://www.digi.com/smart-solutions)

1-866-806-2653