

SPECIFICATIONS 2017

Digi Smart Link Wireless Gateway

Digi Smart Link is the wireless gateway located at each site, which allows Digi Smart Guard to communicate with Digi Smart Command.

Features

- AES 128 bit encryption and robust RX filtering.
- Built in secured web GUI for easily making network setting changes.



Specifications

- | | |
|--------------------------|--|
| • Screen | 2x24 character display with backlight |
| • Backlight | Yes, blue |
| • Wired Communication | Ethernet 10/100 Mbps |
| | USB host x 1, full speed |
| | USB device x 1, full speed |
| • Wireless Communication | ZigBee |
| | Cellular (CDMA) optional module required for this feature |
| • Operating System | Uses a custom embedded Linux operating system |
| • Configuration | DHCP to obtain an IP address (can be configured to use a static IP address and a proxy server) |
| | Uses HTTP or HTTPS to communicate to Digi Smart Command |
| • Communication | 2.4 GHz ZigBee external antenna |
| • Antenna | 5,000 feet line of sight* |
| • Distance | Power adapter is included |
| • Power | 5.25" x 6.33" x 1.5" |
| • Dimensions | 12.4 oz |
| • Weight | RoHS/FCC/IC |
| • Compliances | |

* Actual communication distance will depend on RF environment

For more information about Digi Smart Link
visit www.digi.com/smart-solutions

1-866-806-2653