

SPECIFICATIONS 2017

Digi Smart Shield Pro Wireless HACCP Thermocouple

Digi Smart Shield Pro uses the latest touchscreen Android device, along with a custom Digi Smart Shield Pro application, and Bluetooth wireless temperature probe. HACCP is made easy by using cloud technology to download menu items, user information, and task lists 24/7/365 via Digi Smart Command. As the unit may be taken from site to site, supervisors can use Digi Smart Shield Pro as a verification device and inspection tool.



Features

- Menu items are automatically sent from Digi Smart Command to Digi Smart Shield Pro via Wi-Fi communication.
- Provides corrective actions at the time temperatures are taken outside the acceptable temperature range.
- Food temperature is automatically sent wirelessly to Digi Smart Command for instant viewing.
- Inspection forms can be customized to help exceed compliance requirements.
- English and Spanish language options available.
- Can hold up to 1000 menu items.

Specifications

• Display	7" HD backlit LCD
• Resolution	1280x800 (216ppi)
• Temperature Range	-100°F to 1000°F (-37°C to 537°C)
• Accuracy	±0.7°F (±0.4°C) operating range (32°F to 212°F)
• Response Time	<2.5 seconds
• Probe Type	K-Type probe
• Fahrenheit/Celsius	Yes
• Sleep Mode	Yes
• Battery Life	8 hours of continuous usage
• Calibration/Verification	Calibrated with ice water method
• Operating System	Google Android 4.1 (Jelly Bean)
• CPU	1.2 GHz Dual Core application processor
• Memory	8GB internal storage
• Communications	Wi-Fi with a/b/g/n Bluetooth®
• Camera	3 megapixel rear-facing

For more information about Digi Smart Shield Pro
visit www.digi.com/smart-solutions

1-866-806-2653